

# POWERVER

## Standard Power Conditioners



For use with any microprocessor-based electronic equipment.

POWERVER Standard Power Conditioners incorporate a low impedance isolation transformer, as well as a surge diverter and power line filter to eliminate noise, spikes and transients before they have a chance to wreak havoc on your equipment.

You can trust these power conditioners to protect your sensitive equipment from the biggest problem computers face; common-mode voltage. Common-mode voltage can cause everything from equipment lockups to data losses to "No Trouble Found" service calls.

All North American models have UL and cUL listings. International models are safety-agency listed and carry the CE mark.

- Product sizes range from 78 VA to 2500 VA
- Suitable for use with instrumentation, analyzers, Point-of-Sale (POS) systems, ATMs, security systems, etc.
- Prevents hardware destruction, component degradation and operational disruption
- Red flashing LED (amber for international models) warns if the AC outlet is missing its input safety ground
- Let through voltage is less than 10 volts normal mode and less than 0.5 volts neutral-to-ground when tested to ANSI/IEEE C62.41
- POWERVER's five-year warranty on parts and labor provides complete peace of mind

North American	Load Current (Amps)	Load Power (VA)	Input Voltage (VAC)	Output Voltage (VAC)	Frequency (Hz)	Case Size	Ship Weight (lb)
ABC065-11	.65	78	120	120	60	A	5
ABC100-11	1.0	120	120	120	60	A	6
ABC150-11	1.5	180	120	120	60	A	6
ABC152-11	1.5	180	120	120	60	B	8
ABC201-11	2.0	240	120	120	60	A	7
ABC202-11	2.0	240	120	120	60	B	9
ABC302-11	3.0	360	120	120	60	B	11
ABC402-11	4.0	480	120	120	60	B	12
ABC400-11	4.0	480	120	120	60	C	16
ABC500-11	5.0	600	120	120	60	C	18
ABC600-11	6.0	720	120	120	60	C	20
ABC700-11	7.0	840	120	120	60	C	22
ABC830-11	8.3	1000	120	120	60	D	34
ABC1000-11	10.0	1200	120	120	60	D	38
ABC1200-11	12.0	1440	120	120	60	D	43
ABC1600-11	16.0	1920	120	120	60	D	52
ABC2000-11	20.0	2400	120	120	60	D	63

International	Load Current (Amps)	Load Power (VA)	Input Voltage (VAC)	Output Voltage (VAC)	Frequency (Hz)	Case Size	Ship Weight (kg)
ABC150-22INT	.65	150	230	230	50/60	A	5
ABC250-22INT	1.1	250	230	230	50/60	B	5
ABC500-22INT	2.1	500	230	230	50/60	C	9
ABC750-22INT	3.1	750	230	230	50/60	C	10
ABC1000-22INT	4.2	1000	230	230	50/60	D	17
ABC1250-22INT	5.1	1250	230	230	50/60	D	18
ABC1500-22INT	6.3	1500	230	230	50/60	D	20
ABC2000-22INT	8.3	2000	230	230	50/60	D	23
ABC2500-22INT	10.4	2500	230	230	50/60	D	28

**Case Dimensions** (H x W x D) - in. (mm.):

A Case - 3.61 x 4.25 x 6.74 (92 X 108 X 171)  
 B Case - 4.23 x 4.97 x 7.58 (107 x 126 x 193)  
 C Case - 4.29 x 8.10 x 11.80 (109 x 206 x 300)  
 D Case - 5.60 x 11.15 x 16.10 (142 x 283 x 409)

**Wall Mount Option:**

Available on all models.