

POWERVER

Security One Medical Rackmount (Class A & B) UPM

POWERVER UNINTERRUPTIBLE POWER MANAGER: WHAT A DIFFERENCE A LETTER MAKES.



For use with microprocessor-based medical equipment requiring conformance with UL60601 and IEC60601.

If you think a UPS is the ultimate in power protection, we've got some news for you: Our Security One Medical Rackmount UPM, or Uninterruptible Power Manager, performs functions your old UPS never dreamed of. These rackmount UPMs are designed in a convenient 3U rackmount factor form.

For medical systems used in the vicinity of a patient (or anywhere that low leakage current is required), our medical rackmount UPMs are the perfect solution for providing completely conditioned, uninterruptible power.

North American models are listed to UL60601-1 and cUL22.2 No. 60601-1 and are suitable for patient vicinity applications. International models are listed to IEC60601-1 and are CE marked. All models reduce connected equipment leakage current to less than 300 μ amps.

- Product sizes range from 600 VA to 1440 VA
- True sine-wave output
- Low impedance isolation transformer and line interactive operation
- FCC Class A and Class B models are available
- Meets NEMA, FAA, and DOT guidelines for transportation of UPS batteries
- 19" rackmount design
- Let through voltage is less than 10 volts normal mode and less than 0.5 volts neutral-to-ground when tested to ANSI/IEEE C62.41
- POWERVER's five-year warranty (two-year on batteries) on parts and labor provides complete peace of mind





North American	Load Power (VA/Watts)	Input Voltage (VAC)	Output Voltage (VAC)	Size (in.) (H x W x D)	Ship Weight (lb)
ABCE600-11IECR	600/420	120	120	5.20 (3U) x 19.00 x 19.51	62
ABCE800-11IECR	800/560	120	120	5.20 (3U) x 19.00 x 19.51	67
ABCE1100-11IECR	1100/770	120	120	5.20 (3U) x 19.00 x 19.51	80
ABCE1440-11IECR	1440/1008	120	120	5.20 (3U) x 19.00 x 19.51	94

International	Load Power (VA/Watts)	Input Voltage (VAC)	Output Voltage (VAC)	Size (in.) (H x W x D)	Ship Weight (kg)
ABCE600-22IECR	600/420	230	230	132.10 (3U) x 482.60 x 495.55	25.4
ABCE800-22IECR	800/560	230	230	132.10 (3U) x 482.60 x 495.55	27.2
ABCE1100-22IECR	1100/770	230	230	132.10 (3U) x 482.60 x 495.55	32.7
ABCE1440-22IECR	1440/1008	230	230	132.10 (3U) x 482.60 x 495.55	39