

POWERVAR

Security One Rackmount UPM

**POWERVAR UNINTERRUPTIBLE POWER MANAGER:
WHAT A DIFFERENCE A LETTER MAKES.**



Achieving a power conditioning solution in a rackmount enclosure

If you think a UPS is the ultimate in power protection, we've got some news for you: Our Security One Rackmount UPM, or Uninterruptible Power Manager, performs functions your UPS never dreamed of. These rackmount UPMs are designed in a convenient 3U rackmount form factor.

The Security One Rackmount UPM incorporates a low impedance isolation transformer, noise filter and surge diverter to assure power disturbances will be limited to less than 10 volts normal mode and less than 0.5 volts (common-mode) neutral-to-ground allowing the UPM to deliver completely conditioned power, something few UPS products can do.

All North American models have UL and cUL listings. International models are safety-agency listed and carry the CE mark.

- Product sizes range from 600 VA to 1440 VA
- Low impedance isolation transformer and line interactive operation
- True sine-wave output
- User hot-swappable battery
- Meets FCC Class A (Class B Optional)
- Meets NEMA, FAA and DOT guidelines for transportation of UPS batteries
- 19" rackmount design
- Five-year warranty on electronics and two-year warranty on battery



North American	Load Power (VA/Watts)	Input Voltage (VAC)	Output Voltage (VAC)	Frequency (Hz)	Size (in.) (H x W x D)	Ship Weight (lb)
ABCE600-11R	600/420	120	120	60	5.20 (3U) x 19.00 x 19.51	62
ABCE800-11R	800/560	120	120	60	5.20 (3U) x 19.00 x 19.51	67
ABCE1100-11R	1100/770	120	120	60	5.20 (3U) x 19.00 x 19.51	80
ABCE1440-11R	1440/1008	120	120	60	5.20 (3U) x 19.00 x 19.51	94

International	Load Power (VA/Watts)	Input Voltage (VAC)	Output Voltage (VAC)	Frequency (Hz)	Size (in.) (H x W x D)	Ship Weight (kg)
ABCE600-22R	600/420	230	230	50/60	132.10 (3U) x 482.60 x 495.55	28
ABCE800-22R	800/560	230	230	50/60	132.10 (3U) x 482.60 x 495.55	31
ABCE1100-22R	1100/770	230	230	50/60	132.10 (3U) x 482.60 x 495.55	37
ABCE1440-22R	1440/1008	230	230	50/60	132.10 (3U) x 482.60 x 495.55	43