

POWERVAR

Security One Standard UPM

**POWERVAR UNINTERRUPTIBLE
POWER MANAGER: WHAT A
DIFFERENCE A LETTER MAKES.**



Prevents power disturbances from affecting the performance of mission critical devices


If you think a UPS is the ultimate in power protection, we've got some news for you: Our Security One UPM, or Uninterruptible Power Manager, performs functions your UPS never dreamed of.

Why settle for backup power alone when the POWERVAR Security One Standard UPM lets you manage the entire power interface? Thanks to its low impedance isolation transformer, this UPM delivers clean, fully conditioned power which is free from noise, voltage spikes and common-mode disturbances. If the power goes out, backup battery is one of the many benefits you will receive.

All North American models have UL and cUL listings. International models are safety-agency listed and carry the CE mark.

- Product sizes range from 420 VA to 3000 VA
- True sine-wave output
- Low impedance isolation transformer and line interactive operation
- User hot-swappable battery
- Meets FCC Class A (optional Class B available)
- Meets NEMA, FAA, and DOT guidelines for transportation of UPS batteries
- Let through voltage is less than 10 volts normal mode and less than 0.5 volts neutral-to-ground when tested to ANSI/IEEE C62.41
- POWERVAR's five-year warranty (two-year on batteries) on parts and labor provides complete peace of mind





North American	Load Current (Amps)	Load Power (VA)	Input Voltage (VAC)	Output Voltage (VAC)	Frequency (Hz)	Case Size	Ship Weight (lb)
ABCE420-11	3.5	420	120	120	60	B	32
ABCE600-11	5.0	600	120	120	60	C	41
ABCE800-11	6.7	800	120	120	60	C	47
ABCE1100-11	9.2	1100	120	120	60	D	73
ABCE1440-11	10.6	1440	120	120	60	D	79
ABCE2200-11	18	2160	120	120	50/60	E	160
ABCE3000-11	23	2760	120	120	50/60	E	165

International	Load Current (Amps)	Load Power (VA)	Input Voltage (VAC)	Output Voltage (VAC)	Frequency (Hz)	Case Size	Ship Weight (kg)
ABCE420-22	1.8	420	230	230	50/60	B	14.5
ABCE600-22	2.6	600	230	230	50/60	C	18.5
ABCE800-22	3.5	800	230	230	50/60	C	21.5
ABCE1100-22	4.8	1100	230	230	50/60	D	33.5
ABCE1440-22	6.3	1440	230	230	50/60	D	36.0
ABCE2200-22	9.57	2200	230	230	50/60	E	72.5
ABCE3000-22	13.0	3000	230	230	50/60	E	74.8

Case Dimensions (H x W x D) - in. (mm.):

B Case - 6.60 x 5.50 x 17.75 (168 x 140 x 451)

C Case - 8.00 x 5.80 x 17.50 (203 x 147 x 445)

D Case - 8.75 x 8.30 x 19.75 (222 x 211 x 502)

E Case - 19.25 x 8.26 x 22.00 (489 x 210 x 559)