

# Sentry Metered CDU

## Key Features

- > **Input Current Monitor:** Precisely measure the aggregate current draw (in amps) on each power circuit. On-site verification of the input current with the LED digital display.
- > **Power Distribution:** 120V, 208V, or three phase power with 20 or 30 Amp power input feed options.
- > **Mid-Density:** Single power input feed; 24 outlets per enclosure.

## C-24V

C-24V2-C20

### Mid-Density Metered Power Distribution

Increasing power demands and density in the equipment cabinet requires new functionality from your cabinet PDU. The Sentry CDU product family uniquely meets these demands.

The Sentry Cabinet Power Distribution Unit (CDU) is an intelligent PDU with local LED input current monitoring, allowing network engineers to utilize the CDU's True RMS Power Monitor to precisely measure the current (in amps) that network devices are drawing on the power circuit. As new servers and devices are added to the power drop, immediately observe its impact on the cumulative current draw. This allows the engineer to safely load each circuit to its maximum allowable load capacity without the danger of overloading the power circuit.

### Additional Benefits:



#### Branch Circuit Protection

The Sentry CDU Family meets the new UL 60950-1 requirement for branch circuit protection.

**Attention!** The Sentry CDU products meet the above criteria by providing overcurrent protection with UL-listed Bussman SC fuses for each branch circuit.



#### Input Current Monitoring

The CDU's exclusive True RMS current monitoring is critical to preventing overloads in high-density computing environments. LED digital displays on the CDU enclosure report the input current of each phase or branch circuit.



Model	Available Input Voltages	Amperage	Available Input Cord	Outlets	Dimensions (L x W x D)
C-24V1-C20	100-120V 50/60Hz	20A	IEC 60320/C20 Power Inlet	(24) NEMA 5-20R	54.0" x 1.75" x 2.25"
C-24V1-L530	100-120V 50/60Hz	30A	NEMA L5-30P Cordset	(24) NEMA 5-20R	54.0" x 1.75" x 2.25"
C-24V2-C20	208-240V 50/60Hz	20A	IEC 60320/C20 Power Inlet	(24) IEC 60320/C13	54.0" x 1.75" x 2.25"
C-24V2-L630	208-240V 50/60Hz	30A	NEMA L6-30P Cordset	(24) IEC 60320/C13	54.0" x 1.75" x 2.25"
C-24VE-C20*	230V 50/60Hz	20A	IEC 60320/C20 Power Inlet	(24) IEC 60320/C13	54.0" x 1.75" x 2.25"

\*European Models

## Additional Specifications

### Agency Approvals

- > US & Canada (cTUVus mark) to UL 60950-1:2003 and CAN/CSA 22.2 No. 60950-1-03
- > European Union (TUVGS mark) to EN 60950-1:2001
- > FCC Class A, Part 15
- > CE
- > EMC - EN 55022 Class A, EN 55024

### Power Cord Options

- > PTCORD-1 IEC 60320/C19 - NEMA L6-20P , 10'
- > PTCORD-2 IEC 60320/C19 - Schuko 10'
- > PTCORD-3 IEC 60320/C19 - IEC 60309 (BS4343, CEE17) 16/20A Blue (UK Commando) 10'
- > PTCORD-4 IEC 60320/C19 - BS1363 13A (UK) 10'
- > PT-ADP-C19 Cable mount IEC 60320/C19 Connector

### Branch Circuit Protection

- > Compliant to UL 60950-1


**Server Technology**

<b>EMEA</b>	<b>NORTH AMERICA / ASIA</b>
<b>Server Technology Intl</b>	<b>Server Technology, Inc.</b>
Sienna Court	1040 Sandhill Drive
The Broadway	Reno, NV 89521
Maidenhead	United States
Berkshire	1.775.284.2000 Tel
SL6 1NJ	1.775.284.2065 Fax
United Kingdom	sales@servertech.com
+44 (0) 1628 509053 Tel	www.servertech.com
+44 (0) 1628 509100 Fax	www.servertechblog.com
salesintl@servertech.com	