

Sentry Smart CDU

Key Features

- > **Input Current Monitor:** Precisely measure the aggregate current draw (in amps) on each power circuit. On-site verification of the input current with the LED digital display. Remote verification via web browser or serial screen.
- > **High Power Distribution:** 208V and three-phase power options; 20 or 30-Amp power input feed options.
- > **High Density:** Dual input feed; 84 outlets per enclosure
- > **IP Access & Security:** Web interface, SSL, SSH, Telnet, SNMP, FTP, SNTp, Syslog, LDAP, LDAPS, TACACS and RS-232 access
- > **Environmental Monitoring:** Each Smart CDU supports two external temperature & humidity probes and reports conditions thru the Web interface
- > **Enterprise View:** View and access multiple Smart CDUs from one Web interface.**
- > **SNMP Traps:** Provide automated alerts for power and environmental conditions

CS-84VD

High-Density Power Distribution

The Smart Cabinet Distribution Units (CDU) provide reliable power distribution combined with local and remote power monitoring and environmental monitoring via IP. Use the network interface to view power, temperature and humidity levels via Web browser, or receive SNMP-based alarms when conditions exceed defined thresholds.

The Smart CDU is also supported by our Enterprise View CDU Manager. This gives the network administrator the ability to view and access multiple Smart CDU's from multiple locations via a single Web interface.

Additional Benefits:



Branch Circuit Protection

The Sentry CDU Family meets the new UL 60950-1 requirement for branch circuit protection.

Attention! The Sentry CDU products meet the above criteria by providing overcurrent protection with UL-listed Bussman SC fuses for each branch circuit.



Input Current Monitoring

The CDU's exclusive True RMS current monitoring is critical to preventing overloads in high-density computing environments. LED digital displays on the CDU enclosure report the input current of each phase or branch circuit.



Temperature and Humidity

The Smart CDU supports two external probes. Each of these probes measure both temperature and humidity. Receive SNMP-based alert notifications when conditions exceed defined thresholds.



Model	Available Input Voltages	Amperage	Available Input Cord	Outlets	Dimensions (L x W x D)
CS-84VD2-L620	208-240V 50/60Hz	20A	NEMA L6-20P Cordset	(84) IEC 60320/C13	66.0" x 3.5" x 2.25"
CS-84VD2-L630	208-240V 50/60Hz	30A	NEMA L6-30P Cordset	(84) IEC 60320/C13	66.0" x 3.5" x 2.25"
CS-84VDD-L1520	3-Phase Delta, 208V 50/60Hz	20A	NEMA L15-20P Cordset	(84) IEC 60320/C13	66.0" x 3.5" x 2.25"
CS-84VDD-L1530	3-Phase Delta, 208V 50/60Hz	30A	NEMA L15-30P Cordset	(84) IEC 60320/C13	66.0" x 3.5" x 2.25"
CS-84VDY-L2120	3-Phase Wye, 208V 50/60Hz	20A	NEMA L21-20P Cordset	(84) IEC 60320/C13	66.0" x 3.5" x 2.25"
CS-84VDY-L2130	3-Phase Wye, 208V 50/60Hz	30A	NEMA L21-30P Cordset	(84) IEC 60320/C13	66.0" x 3.5" x 2.25"

Additional Features and Specifications

Agency Approvals

- > US & Canada (cTUVs mark) to UL 60950-1:2003 and CAN/CSA 22.2 No. 60950-1-03
- > European Union (TUVGS mark) to EN 60950-1:2001
- > FCC Class A, Part 15
- > CE
- > EMC - EN 55022 Class A, EN 55024

Communications and Security

- > 10/100 BaseT Ethernet
- > HTTP/HTTPS
- > SSLv3/TLSv1
- > SNMPv2
- > SSHv2
- > Telnet
- > LDAPv3/LDAPS
- > TACACS+
- > RS-232 (Serial)

Branch Circuit Protection

- > Compliant to UL 60950-1

Power Cord Options

- > PTCORD-1 IEC 60320/C19 - NEMA L6-20P , 10'
- > PTCORD-2 IEC 60320/C19 - Schuko 10'
- > PTCORD-3 IEC 60320/C19 - IEC 60309 (BS4343, CEE17) 16/20A Blue (UK Commando) 10'
- > PTCORD-4 IEC 60320/C19 - BS1363 13A (UK) 10'
- > PTCORD-5 IEC 60320/C19 - 5-15P (15A Straight-Blade) 10'
- > PTCORD-6 IEC 60320/C19 - 5-20P (20A Straight-Blade) 10'
- > PTCORD-7 IEC 60320/C19 - L5-20P (20A Twist-Lock) 10'
- > PT-ADP-C19 Cable mount IEC 60320/C19 Connector

Accessories

- > Optional Temperature & Humidity Probe
EMTH-1-1 Temperature & Humidity Probe, 10'


Server Technology

EMEA	NORTH AMERICA / ASIA
Server Technology Intl	Server Technology, Inc.
Sienna Court	1040 Sandhill Drive
The Broadway	Reno, NV 89521
Maidenhead	United States
Berkshire	1.775.284.2000 Tel
SL6 1NJ	1.775.284.2065 Fax
United Kingdom	sales@servertech.com
+44 (0) 1628 509053 Tel	www.servertech.com
+44 (0) 1628 509100 Fax	www.servertechblog.com
salesintl@servertech.com	